








Price list - Sensory system

Voimassa 1.10.2021 alkaen

Pos.	Photo	Art. No.	Article	Drawing	Main application												Gross price Hinta € alv 0	per	Qty unit	Prov. Group	
						SL	SLX	SLX-M	SLX-V	SLX-D	SLA	SLM	FD 10	FD 20	SRM	FFM					Gates
002		45-6466-501	COMBISCAN-SM Motion detector and closing edge monitoring For surface-type mounting incl. connection cable, length: 1,6 m			X	X	X	X	X								400,00	1	ST	10
032		45-6466-303	Domino 1000 CAN Sensor Surface-type mounting against wall or suport profile Without CAN-cable	P 20.04.37				X	X	X	X							TILAUSTUOTE	1	ST	10
038		45-6466-110	Door sensor EAGLE ONE Direction-sensitive microwave doppler radar Surface-type mounting against wall, support profile or ceiling Mounting height 1,8 – 4 m Colour: black with cable 2,5 m	P 20.04.29							X	X	X	X	X	X		213,33	1	ST	10
070		45-6466-213	IXIO-DT3 Combi-Sensor Wall or support profile mounting. As light barrier substitute or additional safety element (e.g. retirement home, hospital etc.) Direction-sensitive door sensor with double protection curtain as opening element and closing edge monitoring. Configurable for standard and redundant sliding doors With cable 2.5 m	P 20.04.61		X	X	X	X	X	X	X			X	X	X	TILAUSTUOTE	1	ST	10


Price list - Sensory system

Voimassa 1.10.2021 alkaen

Pos.	Photo	Art. No.	Article	Drawing	Main application											Gross price Hinta € alv 0	per	Qty unit	Prov. Group			
					SL	SLX	SLX-M	SLX-V	SLX-D	SLA	SLM	FD 10	FD 20	SRM	FFM					Gates		
071		45-6466-212	IXIO-DT1 Combi-Sensor Colour: black Wall or support profile mounting. As light barrier substitute or additional safety element (e.g. retirement home, hospital etc.) Direction-sensitive door sensor with double protection curtain as opening element and closing edge monitoring. With cable 2.5 m	P 20.04.61		X	X	X	X	X	X	X				X	X	X	TILAUSTUOTE	1	ST	10
		45-6466-212/01	IXIO-DT1 Combi-Sensor white	P 20.04.61		X	X	X	X	X	X				X	X	X	TILAUSTUOTE	1	ST	10	
072		45-6466-431	Safety curtain IXIO-ST Wall or support profile mounting. As light barrier substitute or additional safety element (e.g. retirement home, hospital etc.) Double protection curtain With cable 2.5 m	P 20.04.61		X	X	X	X	X	X				X	X	X	TILAUSTUOTE	1	ST	10	
090		45-6452-275	Sensor strip 4SAFE KIT L=350 mm Mounted on the (moving) swing door leaf Protection by a monitored infrared distance measuring Protection field: 400x70 mm (with mounting height 2 m) In aluminium profile with transparent profile and lateral covering caps Mounting height: 1,3 - 3,5 m Colour: black With connection cable (Master-Slave) 450 mm and connection cable, length 2,5 m as well as flexible cable junction	P 20.04.50									X	X				280,00	1	ST	10	

Price list - Sensory system

Voimassa 1.10.2021 alkaen

Pos.	Photo	Art. No.	Article	Drawing	Main application											Gross price Hinta € alv 0	per	Qty unit	Prov. Group	
					SL	SLX	SLX-M	SLX-V	SLX-D	SLA	SLM	FD 10	FD 20	SRM	FFM					Gates
101		45-6466-929	Remote control for EAGLE for BEA devices	e.g. P 20.04.30													TILAUSTUOTE	1	ST	10